



## Teltonika GSM Camera



Teltonika GSM Camera - compact mobile monitoring system for transmission of high resolution static photos via GPRS/EDGE network. You can access your photos from PC or hand held device.

Pictures of desired objects can be transmitted to :

- E-Mail
- FTP server (passive mode)
- PC with an access to internet
- WEB server
- Video server (a separate device to be designed soon).

Camera application:

- Remote control
- Security
- Surveillance
- Passageway control
- Traffic control (e.g. "traffic jam" inspection)
- etc.

#### ADDITIONAL FUNCTIONS:

- Integrated microphone for audio surveillance of premises.
- Selectable photo formats (80x64, 160x128, 320x240, 640x480) for transmission.
- Programmable period of automatic photo transmissions (intervals from 1 min to 24 hours).
- Remote camera activation through SMS or short call.
- List of authorized numbers (up to 20). Full configuration of the camera is enabled only from one number. From all other authorized numbers it is possible to receive messages about system initialization, request filming and listen to sounds in premises.
- You can control GSM Camera:
  - o by SMS commands from mobile phone
  - o using PC program "Camera Configurator" (included in the device package)
  - o from Video server (in the future)
- External sensors can be connected to the camera. System reaction to sensors is programmed by a user over SMS messages or "Camera Configurator" software.
- Camera can be connected to external control system (e.g. security console) and function as a part of the whole system.
- Additional video module Mini Camera or Cupol Camera can be connected to the device for supplementing observation points. Additional module will be recognized by the system automatically.



## Teltonika GSM Camera

#### TECHNICAL SPECIFICATION:

<b>Power supply</b>	9-30V, 1W
<b>Case</b>	Metal, dimensions 120x55x45mm (without mounting bracket)
<b>Operating temperature</b>	0 - +40C
<b>Photo formats</b>	JPEG 16bit color 80x64/160x128/320x240/640x480 pixels
<b>Control contacts for external light</b>	0-30V, 5A